

# KOHLER RENTAL



## TEMPERATURE CONTROL SOLUTIONS

Kohler Rental is your single source, full-service provider of reliable temperature control products, accessories and companion systems for immediate solutions to your heating, cooling and refrigeration needs. Kohler offers a full variety of KOHLER® generators, power distribution, state-of-the-art air conditioning units, chillers, heaters and luxury restrooms. In addition to state-of-the-art equipment, our technical services and design team provides a complete solution, taking the burden out of planning.

### Applications:

Kohler Rental is an experienced temperature control provider for industrial, commercial, event and emergency applications.

#### Industrial/Commercial

- Planned or emergency HVAC system downtime
- Seasonal, occasional or nonrecurring applications
- Industrial process supplement or pilot project support
- Temporary or transitional construction related needs
- Spot cooling and spot heating in extreme conditions
- Thermal storage applications

#### Event

- Ice-making capabilities
- Spot cooling and spot heating in extreme conditions
- Maintain a comfortable environment in a building or a tent

#### Emergency

- Temporary replacement of industrial process cooling equipment
- Spot cooling and spot heating in extreme conditions
- Maintain a comfortable environment in a building or tent
- Dehumidification of buildings

### Product Features:

#### Air Conditioners

- Easy to operate with fully automatic or manual override control
- Individual circuit breaker protection
- Quick setup with color-coded, cam-type electrical connections
- Air conditioning units with heating capabilities
- Allows for securing tent flaps to the edge of the unit (5- to 25-ton ductless units)
- Integrated or remote thermostatic controls (5- to 25-ton ductless units)
- Multiple supply and return air connections (30- and 60-ton ductable units)

#### Chillers

- Digital controller keeps the chiller safely online
- Dependable and reliable screw compressor
- Limited additional clearance needed around the unit for proper air flow
- High and low ambient temperature operation capabilities

#### Air Handlers

- Fully ductable with side- or end-duct configurations

#### Heaters

- Internally insulated ductable venting with a variable speed fan and main unit power circuit breaker (150 kW)

- Thermostatic control and protection from overheating
- Portable construction style design for 10 to 18 kW heaters

#### Accessories and Companion Systems

Pumps, heat diffusers, generators, power modules, switchgear, transformers, distribution panels and cable.

#### Other Temperature Control Equipment

- Cooling Towers
- Boilers
- Spot Coolers
- Heat Exchangers
- Water Manifolds
- Hoses & Ducting

#### Technical Services and Design

At Kohler Rental, state-of-the-art equipment is only part of the solution. Our technical services and design team provides a complete solution for your needs, including process cooling and environmental temperature control. But we don't stop there, we'll assist you through the equipment selection process, as well as your project's schematics and submittal package, all backed by our mechanical engineering capabilities. Truly turnkey, our team of experts takes the burden out of planning, saving you time and money.

Seven regional offices and more than 80 sales and service locations nationwide.

**CORPORATE OFFICE:**  
KOHLER, WISCONSIN

888-769-3794

[fax] 920-459-1846

HOUSTON, TEXAS

866-592-7050

[fax] 972-790-5754

PHOENIX, ARIZONA

866-487-8844

[fax] 702-260-7829

WASHINGTON, DC

866-732-8734

[fax] 410-969-7276

CHICAGO, ILLINOIS

877-620-7449

[fax] 630-226-1596

DALLAS, TEXAS

866-592-7050

[fax] 972-790-5754

LOS ANGELES, CALIFORNIA

866-577-4797

[fax] 310-518-5028

ORLANDO, FLORIDA

866-850-8132

[fax] 407-281-8851

**YOUR WORLD. UNINTERRUPTED.**

# YOUR WORLD. UNINTERRUPTED.

## TEMPERATURE CONTROL SOLUTIONS

### Products



#### Air Conditioners

5- to 25-ton ductless air conditioners feature an integral or remote thermostatic control that can be manually operated for continuous heating or cooling.

15- to 60-ton ductable units are also available for venues requiring remote location of the HVAC system.



#### Air Handlers

50- and 100-ton air handlers — fully ductable, with side- or end-duct connections. High pressure forward-curved blower with fan speed control. Horizontal cabinet-style encasement.



#### Chillers

100-, 200- and 300-ton air-cooled chillers provide chilled water for cooling. Industrial, commercial, event or emergency applications.



#### Heaters

10 to 150 kW portable electronic heater units provide sufficient heating solutions for any personal, commercial, industrial or event need. Horizontal cabinet-style encasement with thermostatic control and protection from overheating.

AC Units						
Model	Cooling/Heating	Air Flow (CFM)	Voltage/Phase/Freq/Amps	Dimensions (L x W x H)	Weight (lb)	Cooling Operating Temp Degrees F (Max/Min)
10 Ton - Ductless	118,000 Btu/30 kW	4,000	208-230/3/60/100	2'8" x 5'4" x 6'11"	1,275	110/65
20 Ton - Ductless	238,000 Btu/33 kW	8,000	208-230/3/60/125	2'8" x 7'8" x 7'11"	2,500	110/65
25 Ton - Ductless	294,100 Btu/45 kW	9,000	208-230/3/60/166	4'2" x 9' x 7'8"	3,300	110/65
15 Ton - Ductable	250,000 Btu/20 kW	5,000	460/3/60/67	8'3" x 8' x 5'6"	4,000	120/0
30 Ton - Ductable	372,000 Btu/45 kW	8,160	460/3/60/127	8'3" x 8'6" x 7'2"	5,000	120/0
30 Ton - Ductable	360,000 Btu/72 kW	10,000	460/3/60/111	13'9" x 8' x 5'10"	5,400	120/0
60 Ton - Ductable	695,000 Btu/150 kW	21,000	460/3/60/221	22' x 8'6" x 8'3"	9,250	120/0
Chiller Units						
Model	Cooling BTU	Recommended Water Flow (GPM) Requirements*	Voltage/Phase/Freq/Amps	Dimensions (L x W x H)**	Weight (lb)**	Max Operating Temp Degrees F
100 Ton	1,200,000	244	480/3/60/250	18'3" x 8'3" x 8'3"	9,310	115/-10
200 Ton	2,400,000	443	480/3/60/500	20'7" x 8'3" x 8'8"	14,950	125/0
300 Ton	3,600,000	688	480/3/60/700	38' x 8'3" x 8'9"	22,900	125/0
Air Handler Units						
Model	Cooling BTU	Air Flow (CFM)	Voltage/Phase/Freq/Amps	Dimensions (L x W x H)	Weight (lb)	
50 Ton	600,000	13,500	480/3/60/32	10' x 6'6" x 5'8"	4,500	
100 Ton	1,200,000	27,000	480/3/60/40	12' x 6'6" x 8'	5,900	
Electric Heaters						
Model	Heating	Air Flow (CFM)	Voltage/Phase/Freq/Amps	Dimensions (L x W x H)	Weight (lb)	Max Leaving Air Temp Degrees F
10 kW	34,000 Btu/10 kW	800	208/3/60/42	2'3" x 1'9" x 3'3"	60	100
15 kW	51,000 Btu/15 kW	800	208/3/60/42	2'3" x 1'9" x 3'3"	65	100
18 kW	61,000 Btu/18 kW	740	240/1/60/47	2'6" x 1'2" x 1'6"	52	212
40 kW	136,000 Btu/40 kW	1,765	480/3/60/60	3'10" x 1'8" x 2'1"	125	212
150 kW	512,000 Btu/150 kW	9,000	480/3/60/248	6' x 4' x 4'2"	1,350	160

\*Dependent on pumps used.

\*\*Does not include trailer. Units can be used on or off trailer.

Specs and features vary by product model and year manufactured. Call Kohler Rental for specs of available equipment.